韩国独资

YIXING
Packing Machinery
乙星包装机械

常熟乙星包装机械有限公司
地址：江苏省常熟市董浜镇徐市工业园旗杆二路8号
电话：0512-52674348 52674338 52674358
传真：0512-52674378
邮箱：es.propack@yahoo.com.cn
公司网站：http://www.propackco.com

深圳办事处
地址：深圳市龙岗区平湖华南城P16-128号
电话：0755-89689690
传真：0755-89689690
邮箱：szeulsung@163.com

Changshu Yixing Packing Machinery Co., Ltd
Head office/Factory
Add: No.8 of Qigan Second Rd, XuShi Industrial Area, Dongbang, Changshu, Jiangsu Province, P.R.C.
Tel: 0086-512-52674348 52674338 52674358
Fax:0086-512-52674378
E-mail: es.propack@yahoo.com.cn

Shenzhen Office
Add: P16-128, ChinaSouthCity, Longgang District, Shenzhen, Guangdong Province
Tel: 0086-755-89689690
Fax: 0086-755-89689690
E-mail: szeulsung@163.com

Eul sung Auto Pack M/C Corp(Korea)
Add: #48-80, Sam Jung-Dong, Oh Jung-Gu, Buchon-City, Kyung Ki-Do, Korea
Tel: 0082-32-677-5730
Fax:0082-32-677-5734
E-mail: propack@propackco.com
homepage：http://www.propackco.com

常熟乙星包装机械有限公司
Changshu Yixing Packing Machinery Co., Ltd

YIXING
Packing Machinery
乙星包装机械

韩国独资

尊敬的客户：

您好！

我公司是一家韩国独资企业,位于风景秀丽的江南文化名城-江苏省常熟市东郊，交通便捷，沿江高速、苏嘉杭高速穿越境内。

公司成立于2002年初，总部设在韩国富川市，已积累了30余年的包装机械制造经验，产品远销东南亚、拉丁美洲等国家及地区。

目前本公司设计制造的产品包括：连续封口机、枕式包装机、吸塑包装机、杯盘包装机、扎口机、真空包装机、全自动注射器包装机等。机器完全韩国制造或采用韩国先进技术，结构紧密合理，设备稳定耐用，可以帮助客户节省劳力、节约能源，提高生产效率，降低生产成本。


用户的需求即是我们的追求，我们愿同所有新老客户一起分享我们的科技成果，用我们的设备来包装您的产品，用您的成功换来我们共同的喜悦，愿您我携手共创辉煌。

敬祝：

商祺！
常熟乙星包装机械有限公司

Firstly we'd like to be pleased to introduce ourselves to our valuable customers and cooperators.
We are founded at 1992 with the aiming to one stop packaging solution to the world and the Chinese factory is founded at 2002.
One stop packaging is our company's Goal and our all members do their best efforts to make our customers satisfaction through our equipments and support as of now.
Our equipments and service is as follows.
Continuous band sealer, Horizontal flow wrapper, Automatic tray filling and sealing machine, Automatic syringe packing machine, Blister packing machine, Mold change type filling and sealing machine, twisting tie machine, vacuum packing machine and so on.
We already have a good reputation on our equipment's quality and service through our customers.

Sincerely yours,
All members of Eul sung Auto Pack M/C Corp





连续封口机系列
Continuous Band Sealer Series



▲ SPM-100S



▲ SPM-100P



▲ SPM-200P



▲ SPM-100PA



▲ SPM-200S




▲ SPM-300P



▲ SPMV

连续封口机采用韩国技术，关键部件采自韩国。设备稳定，封口美观牢固，适用于食品、医疗、化工等的连续封口作业。消除了走袋偏移、封口出现皱褶等问题。

Continuous Band Sealer with printer is widely used in Food, BIO, Chemical industry and so on. It eliminates the excursion, ungraceful in bag sealing and many problems.




产品特点：

- ◆ 不限制封口长度
- ◆ 自调压力系统：适用于包装任何类型和厚度的袋子
- ◆ 高性能的温控
- ◆ 工作速度可调：适用于高效率的生产线
- ◆ 具有计数功能
- ◆ 使用色带打码机，印字清晰双加热型适用于较厚或M形包装袋
- ◆ 可选项：打码机、脱气装置、双加热、全不锈钢材质

Features:

- ◆ Continuous heating system: Infinite sealing length
- ◆ Self-adjusting pressure system: Suitable for sealing any type and thickness of the bag
- ◆ High quality temperature controller: Keep sealing graceful
- ◆ Adjustable working speed: useful for assembling line with high efficiency
- ◆ Working cycle counter included
- ◆ Hot printer: 1 or 2 lines available; carve a seal printer to make the printing clearly
- ◆ Double heater option is used with the thicker or M shape bag.
- ◆ Option: Hot printer, Air suction system, double heater, Stainless steel...


江苏 常熟： 0512-52674348　广东 深圳：0755-89690690



输送台面可向外调节60-70mm以满足不同长度产品的包装要求。

According to the size of the bag, the width of conveyor can be extended up to 70mm.






输送台面可下调节60mm以满足不同厚度产品的包装要求。

The height of conveyor can adjust up to 60mm to meet the package.





输送台面可倾斜角度(最大15°)，以满足液体、粉末等产品的包装要求。

Conveyor can adjust with the height and make an angle down to 15 degrees.

技术参数： Technical parameters:

型号	SPM-100S	SPM-100P	SPM-100PA	SPM-200S	SPM-200P
电源	AC 220V，1Ph	AC 220V，1Ph	AC 220V，1Ph	AC 220V，1Ph	AC 220V，1Ph
功率	860W	1040W	1410W	920W	1100W
封口宽度	10mm	10mm	10mm	10mm	10mm
工作速度	Max 21米/分钟	Max 21米/分钟	Max 21米/分钟	Max 21米/分钟	Max 21米/分钟
输送带规格（mm）	W220×L1390	W220×L1390	W220×L1390	W220×L1450	W220×L1450
高温布规格（mm）	W20×L1210	W20×L1210	W20×L1390	W20×L1210	W20×L1210
整机尺寸（mm）	W550×L1050×H1050	W550×L1050×H1050	W550×L1050×H1050	W700×L1450×H1500	W700×L1450×H1500
重量（Kg）	73	78	92	111	116
印字方式		色带打码机	色带打码机		色带打码机

江苏 常熟： 0512-52674348　广东 深圳：0755-89690690

扇形扎口机
Twisting tie machine











扇形扎口机能实现用彩色线把包装袋扎口作业达到美观的扇形包装效果。节省了劳动力并大幅提高了生产效率。

It's a Pneumatic type Tying Machine Tying with color wire and Pan Shaping for Upper Bag margin show nice outlook. And Various thickness of wires are available.

产品特点：

- 无电操作，气动控制。扎口形状为扇形，外观美观一致，扇形折叠装置更换简易。简易操作，各种捆线均适合。广泛应用于面包、蔬菜、鱼丸、冻品、膨化食品、干果、糖果等的扇形扎口包装。

Features:


- No need the electricity for the operation. But it's driven by compressed Air.
- Easy to replace the Fan Shaping folder and good to make Fan Shape
  Application: Bread, Fruits, Fishball, Ice Bars, Pop Corn, Mushroom etc

技术参数： Technical parameters:

型号	Model	GET-250A
气源气压	Air Pressure	5-6kgf
允许袋口宽度	Allows the pocket width	Max250mm
工作速度	Working speed	30次/分钟
扎线内芯直径	Inner core diameter of the Twisttie	0.38 0.42 0.45
整机尺寸	Machine size	445×450×950mm
重量	Weight	65kg

江苏 常熟： 0512-52674348　广东 深圳：0755-89689690

外抽式真空充氮包装机系列
Nozzle type vacuum and gas flushing packing machine



▲ EV-45E



▲ GVD-60E



▲真空包装机控制面板
Controller



▲ GHV-1200E



▲ GH-2600H

外抽真空充氮包装机系韩国原装进口，内置高性能真空泵，低噪微震，需要提供气源气动控制。数字控制，LED液晶屏显示，简捷易操作，并有全面的防压手安全设计、热熔断警报、键盘锁定、真空度感应系统。消除了同类产品抽气不充分、吸嘴退后滞留痕迹、封口不平滑不牢固、易损件更换频繁等缺点。

多项功能：封口+抽气（3种模式）+充气（4种模式）+25个快捷记忆功能键

适用电子、医疗、食品、五金等行业

其他选项：双层加热、双吸嘴、不锈钢支架、倾斜式、打码机等。

High productivity and smooth operation using a driving method of an air pressure cylinder → Smooth operation and stabilization by the best know-how in the industry

Stainless steel case with many options ：Stand, angle calibration system (manual, automatic), printer

Easy to use with most functions with state-of-the art digital controller in Korea: Sealing + Vacuum (3 Modes) + Gas Charging (4 Modes) +25 Preset Memories

A compact model easy to handle.

A built-in vacuum pump with a high-power external vacuum pump.

A built-in and detachable innovative vacuum pump with low noise and low vibration.

Widely used from food industry to bio and electronic industry.

Safety design comprehensive enough to meet the standards of advanced countries.

江苏 常熟： 0512-52674348　广东 深圳：0755-89689690

高速全自动注射器包装机
High Speed Automatic Syringe Flow Wrapper





一次性注射器自动包装机ES-101S使用韩国技术，关键部件采自韩国。采用高级PLC操纵装置和精密的结构，可实现一次性注射器装配后的后续作业：排序-筛选-入袋-印字-封切过程，帮客户节省劳动力、节省资源、降低成本。

Advanced PLC control and compact structure to meet labor-save, maintenance-save and cost-save request.

产品特点：

- AC变频装置可调节不同速度
- 调整光电仪可修改指示前后印刷包装材料物质
- 易读易用的控制面板，设置在操作人员方便可及之处
- 注射器组装不良品筛选装置
- 透析纸条包装
- 可选项：悬挂打孔器、2个切割器、筛选空袋装置、注射器定量整列装置

Features:


- Variable speed control by AC inverter
- Adjustable photocell for two-way correction of the register printed wrapping material
- The easy-to read, easy-to-use control panel is placed well within on operator’ s reach
- Screening of non-performing goods assembled syringe device
- Options: Electicity:220V,50Hz,5.5Kw
  Dimension:1100W×6500L×2300H
  Capacity:140-160packs/min
  Air Pressure:6kgf/cm2
- Hanging hole punch
- Tow cutter
- Screening of air bag device
- Quantitative syringe out the whole device

江苏 常熟： 0512-52674348　广东 深圳：0755-89689690

手套自动包装机
Gloves automatic packing machine



▲ ES-101



▲ ES-102

此款机器是我公司专门为手套行业量身定做的一款全自动包装机，核心采用进口部件，运用韩国技术制造。整机稳定，长时间工作时故障率低，大大提高了手套行业的包装效率同时节省了劳动力。

This machine is designed for the gloves packaging using Korean technology and the main parts are imported. It’ s working well for a long time without any malfunction and greatly improved the production efficiency and save the labor.

产品特点：

- 自动进料
- 打孔装置
- 为适应不同规格的产品可调节包装袋的尺寸
- 自动给料，可与高效率生产线连接

Features:


- Automatic feeding
- Holing system
- Adjustable packaging size to meet the different size products
- It can be connected with the high-efficiency line.

技术参数： Technical parameters:

型号	Model	ES-102
薄膜宽度	Film width	MAX 500mm
制袋长度	Bag length	80-420mm
制袋宽度	Bag width	20-170mm
产品高度	Product Height	20-70mm
包装速度	Packaging speed	20-120袋/分钟
电源功率	Power	220V,50HZ,2,6KW
整机尺寸	Machine size	L5800×W1200×H1380mm
机器重量	Weight	1600kg

江苏 常熟： 0512-52674348　广东 深圳：0755-89689690

全自动吸塑包装机 ES-BM422
Blister Packing Machine



该吸塑包装机主要适用于一次性医疗产品（一次性注射器、输液器、医药），食品，纺织，玩具和牙刷等的高速自动包装。

The main application of this machine is packing of disposable medical products, such as disposable syringe, infusion set, pharmacy products, food, textile, toys and tooth brush.

产品特点：

- 本机适用于软式包装和硬型包装
- 可配备打印设备（可直接打印文字和图形）
- 易于控制，触摸屏
- 可延长模具，可包装大型和长条产品
- 一次性成型，适合大规模生产
- 通过改变模具可生产不同类型的产品
- 整机使用不锈钢和铝合金材质，从而确保清洁抑菌
- 电动气动元件使用进口三菱，欧姆龙，SMC等，
  真空泵由BECKER提供，运作良好，长时间工作故障率极低。
  此机可装配余料收集装置

Features:


- Suitable for both soft type packing and hard type packing
- If the printer is equipped to this machine, it can print words and graphs directly
- Easy control with touch screen
  Lengthening mould part to make the packing of large, long products possible
- This machine is covered by stainless steel and aluminum alloy, thus ensure the clean bacterium-free products
- The electric pneumatic components are imported from Mitsubishi,
- Omron, SMC etc...and the vacuum pump is from BECKER,
  working well for a long time without any malfunction.

技术参数： Technical parameters:

最大包装宽度	**Maximum Package Width**	400mm
最小包装宽度	**Minimum package width**	19mm
最大包装长度	**Maximum package length**	398mm
最大的成型深度	**Maximum forming depth**	60mm
最大印刷长度	**Maximum print length**	398mm
最大印刷宽度	**Maximum printing width**	398mm
工作能力	**Ability to work**	16次/分钟 据模具不同
膜宽度	**Film width**	422-423mm
纸张宽度	**Paper width**	410mm
空气压力	**Air pressure**	0.7MPa
冷却水	**Cooling water**	> 5L/Min、< 25℃
重量	**Weight**	2100Kg
电源	**Power supply**	380V 50HZ 9Kw 3P
整机尺寸	**Machine size**	L5700×W1000×H1950

江苏 常熟： 0512-52674348　广东 深圳：0755-89689690

ES-203杯盘包装机
Mold Changing type filling and sealing machines





适用产品：所有可以热封产品，如食品、工业产品等
Applicable product: All heat sealable caned product such as food & industrial goods.

产品特点：

- 工作速度：最大25次/分钟（最大120杯/分钟）
- 薄膜规格：最大薄膜宽度：700mm
  最大输出直径：350mm
  最大重量：30kg
  所有可热封的薄膜均适用
- 电源：220V，3P或380V，3P
- 可选项：颗粒和液体灌装装置,地图系统,编码器，可采用触摸系统

Features:

- Output: Max. 25 cycles/min/1 lane(Max. 120 trays/min at 5 lanes
- Film size:
  Core size: 76mm
  Max. film width:700mm
  Out dia. (Max.): 350mm
  Weight(Max.): 30kg
  All heat sealable film can be used
- Power: Source: 220V 3P or 380V 3P
- Consumption: depend on capacity
- Option: Tray denester
  Filling unit for granule and liquid
  MAP system
  Coding system
  Capping & lidding system
- All machine dimension depended on customer and tray & Opt & required output
- Machine indexing by AC servo controlled
- Touch panel adopted (if required)

江苏 常熟： 0512-52674348　广东 深圳：0755-89689690